

立式储气罐技术参数

(2017-2-24)

| 序号 | 规格 容积-压力 | | 设计 温度 T℃ | 容器 总高 度 H | 容器 内径 DN | 进气口 | | | 出气口 | | | 支座 | | 安全 阀接 口 | 排污 阀接 口 |
|----|-------------|-----|----------------|-----------------|----------------|----------|----------|--------------|----------|----------|-------------|-------------|-------------|---------------|---------------|
| | | | | | | 高度 H1 | 法兰 d1 | 螺纹 d1 | 高度 H1 | 法兰 d2 | 螺纹 d2 | 孔 径 d | 距 离 D | | |
| 1 | 0.3 | 0.8 | 150 | 1560 | 550 | 520 | DN40 | Rp-1 -1/2 | 1216 | DN40 | Rp-1 /2 | 20 | 40 | Rp1 | R1/2 |
| 2 | | 1.0 | | 1561 | | 643 | | | 1217 | | | | | | |
| 3 | | 1.3 | | 1685 | | 643 | | | 1392 | | | | | | |
| 4 | | 1.6 | | 1686 | | 644 | | | 1393 | | | | | | |
| 5 | 0.5 | 0.8 | 150 | 2177 | 600 | 628 | DN40 | Rp1- 1/2 | 1840 | DN40 | Rp-1 /2 | 20 | 42 | Rp1 | R1/2 |
| 6 | | 1.0 | | 2177 | | 628 | | | 1840 | | | | | | |
| 7 | | 1.3 | | 2178 | | 669 | | | 1649 | | | | | | |
| 8 | | 1.6 | | 2178 | | 669 | | | 1845 | | | | | | |
| 9 | 0.6 | 0.8 | 150 | 1843 | 700 | 750 | DN80 | Rp1- 1/2 | 1500 | DN80 | Rp1- 1/2 | 24 | 49 | Rp1 | R1/2 |
| 10 | | 1.0 | | 1858 | | 750 | | | 1500 | | | | | | |
| 11 | | 1.3 | | 1859 | | 750 | | | 1500 | | | | | | |
| 12 | | 1.6 | | 1859 | | 750 | | | 1500 | | | | | | |
| 13 | 1.0 | 0.8 | 150 | 2240 | 800 | 610 | DN80 | Rp1- 1/2 | 1810 | DN80 | Rp1- 1/2 | 24 | 56 | Rp1 | R3/4 |
| 14 | | 1.0 | | 2240 | | 612 | | | 1812 | | | | | | |
| 15 | | 1.3 | | 2340 | | 710 | | | 1912 | | | | | | |
| 16 | | 1.6 | | 2343 | | 712 | | | 1912 | | | | | | |
| 17 | 1.5 | 0.8 | 150 | 2357 | 1000 | 747 | DN80 | Rp2 | 1877 | DN80 | Rp2 | 24 | 70 | Rp1- 1/2 | R3/4 |
| 18 | | 1.0 | | 2357 | | 747 | | | 1877 | | | | | | |
| 19 | | 1.3 | | 2359 | | 748 | | | 1878 | | | | | | |
| 20 | | 1.6 | | 2363 | | 750 | | | 1880 | | | | | | |
| 21 | 2 | 0.8 | 150 | 2592 | 1100 | 837 | DN80 | Rp2 | 2088 | DN80 | Rp2 | 24 | 74 | Rp1- 1/2 | R3/4 |
| 22 | | 1.0 | | 2592 | | 837 | | | 2087 | | | | | | |
| 23 | | 1.3 | | 2694 | | 838 | | | 2188 | | | | | | |
| 24 | | 1.6 | | 2698 | | 840 | | | 2190 | | | | | | |
| 25 | 2.5 | 0.8 | 150 | 2776 | 1200 | 846 | DN100 | | 2246 | DN100 | | 24 | 84 | Rp1- 1/2 | R3/4 |
| 26 | | 1.0 | | 2778 | | 847 | | | 2247 | | | | | | |
| 27 | | 1.3 | | 2782 | | 851 | | | 2249 | | | | | | |
| 28 | | 1.6 | | 2788 | | 854 | | | 2254 | | | | | | |
| 29 | 3 | 0.8 | 150 | 2807 | 1300 | 852 | DN100 | | 2200 | DN100 | | 24 | 95 | Rp1- 1/2 | R3/4 |
| 30 | | 1.0 | | 2809 | | 856 | | | 2200 | | | | | | |
| 31 | | 1.3 | | 2817 | | 856 | | | 2202 | | | | | | |
| 32 | | 1.6 | | 2830 | | 920 | | | 2204 | | | | | | |
| 33 | 4 | 0.8 | 150 | 3040 | 1400 | 930 | DN100 | | 2400 | DN100 | | 24 | 10 | Rp1- 1/2 | R3/4 |
| 34 | | 1.0 | | 3042 | | 930 | | | 2400 | | | | | | |
| 35 | | 1.3 | | 3051 | | 930 | | | 2513 | | | | | | |
| 36 | | 1.6 | | 3051 | | 930 | | | 2466 | | | | | | |

立式储气罐技术参数

(2017-2-24)

| 序号 | 规格 容积压力 | | 设计 温度 T℃ | 容器 总高 度 H | 容器 内径 DN | 进气口 | | | 出气口 | | | 支座 | | 安全 阀接 口 | 排污 阀接 口 |
|----|------------|-----|----------------|-----------------|----------------|----------|----------|----------|----------|----------|----------|---------|-------------|---------------|---------------|
| | | | | | | 高度 H1 | 法兰 d1 | 螺纹 d1 | 高度 H1 | 法兰 d2 | 螺纹 d2 | 孔径 d | 孔距 D | | |
| 37 | 5 | 0.8 | 150 | 3790 | 1400 | 866 | DN100 | | 3210 | DN100 | 24 | 1050 | Rp1- 1/2 | R1 | |
| 38 | | 1.0 | | 3792 | | 866 | | | 3211 | | | | | | |
| 39 | | 1.3 | | 3796 | | 666 | | | 3211 | | | | | | |
| 40 | | 1.6 | | 3801 | | 666 | | | 3211 | | | | | | |
| 41 | 6 | 0.8 | 150 | 4440 | 1400 | 880 | DN125 | | 3840 | DN125 | 24 | 1050 | Rp1- 1/2 | R1 | |
| 42 | | 1.0 | | 4442 | | 881 | | | 3881 | | | | | | |
| 43 | | 1.3 | | 4444 | | 881 | | | 3881 | | | | | | |
| 44 | | 1.6 | | 4451 | | 881 | | | 3840 | | | | | | |
| 45 | 8 | 0.8 | 150 | 4532 | 1600 | 972 | DN150 | | 3849 | DN150 | 30 | 1200 | Rp2 | R1 | |
| 46 | | 1.0 | | 4532 | | 949 | | | 3849 | | | | | | |
| 47 | | 1.3 | | 4532 | | 972 | | | 3849 | | | | | | |
| 48 | | 1.6 | | 4532 | | 972 | | | 3849 | | | | | | |
| 49 | 10 | 0.8 | 150 | 4541 | 1800 | 1008 | DN150 | | 3808 | DN150 | 30 | 1350 | Rp2 | R1 | |
| 50 | | 1.0 | | 4541 | | 1008 | | | 3808 | | | | | | |
| 51 | | 1.3 | | 4545 | | 1008 | | | 3810 | | | | | | |
| 52 | | 1.6 | | 4548 | | 1010 | | | 3846 | | | | | | |
| 53 | 12. | 0.8 | 150 | 4640 | 2000 | 1090 | DN150 | | 3892 | DN150 | 30 | 1500 | Rp2 | R1 | |
| 54 | | 1.0 | | 4640 | | 1090 | | | 3892 | | | | | | |
| 55 | | 1.3 | | 4646 | | 1093 | | | 3844 | | | | | | |
| 56 | | 1.6 | | 4648 | | 1449 | | | 3846 | | | | | | |
| 57 | 15 | 0.8 | 150 | 5389 | 2000 | 1090 | DN150 | | 4590 | DN150 | 30 | 1500 | Rp2 | R1 | |
| 58 | | 1.0 | | 5389 | | 1090 | | | 4590 | | | | | | |
| 59 | | 1.3 | | 5393 | | 1092 | | | 4592 | | | | | | |
| 60 | | 1.6 | | 5395 | | 1103 | | | 4593 | | | | | | |
| 61 | 20 | 0.8 | 150 | 5973 | 2200 | 1225 | DN200 | | 5025 | DN200 | 30 | 1650 | Rp3 | R1 | |
| 62 | | 1.0 | | 5978 | | 1228 | | | 5028 | | | | | | |
| 63 | | 1.3 | | 25981 | | 1230 | | | 5030 | | | | | | |
| 64 | | 1.6 | | 5986 | | 1232 | | | 5032 | | | | | | |
| 65 | 25 | 0.8 | 150 | 6249 | 2400 | 1190 | DN200 | | 5349 | DN200 | 36 | 1800 | Rp3 | R1 | |
| 66 | | 1.0 | | 6249 | | 1200 | | | 5350 | | | | | | |
| 67 | | 1.3 | | 6249 | | 1200 | | | 5350 | | | | | | |
| 68 | | 1.6 | | 6253 | | 1202 | | | 5354 | | | | | | |
| 69 | 30 | 0.8 | 150 | 5698 | 2800 | 1298 | DN200 | | 4698 | DN200 | 36 | 2100 | Rp3 | R1 | |
| 70 | | 1.0 | | 5700 | | 1300 | | | 4698 | | | | | | |
| 71 | | 1.3 | | 5704 | | 1302 | | | 4700 | | | | | | |
| 72 | | 1.6 | | 5708 | | 1306 | | | 4704 | | | | | | |
| 73 | 40 | 0.8 | 150 | 7348 | 2800 | 1298 | DN200 | | 6348 | DN200 | 36 | 2100 | Rp3 | R1 | |
| 74 | | 1.0 | | 7352 | | 1300 | | | 6350 | | | | | | |